

### BETTABOND SAFETY DATA SHEET

#### PRODUCT AND COMPANY INFORMATION

**PRODUCT DETAIL:**

Product Name: Macsim Cool Room Non Skinning Sealant  
Physical Form: Paste  
Odour: Mild Oils Odour

**COMPANY DETAIL:**

Manufacturer: Macsim Fastenings Pty Ltd  
Address: 10 Wonderland Drive, Eastern Creek, NSW, 2766  
Phone: (02) 9881 2400  
Fax: (02) 9881 2444

#### IDENTIFICATION

**Name:** Macsim Bettabond  
**Other name:** Construction Adhesive  
**UN Number:** None assigned  
**Dangerous Goods Class:** None assigned  
**Transport Classification:** None assigned  
**Hazchem Code:** None assigned  
**Subsidiary Risk:** None assigned  
**Poisons Schedule:** Not Scheduled  
**Packaging Group:** Not applicable

**Bettabond is classified as non-hazardous according to Worksafe Australia criteria.**

#### IDENTIFICATION

To be used for bonding various materials in the building industry. It is applied by the use of a caulking gun.

## TECHNICAL DATA SHEETS

### PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Thick paste
<b>Colour:</b>	Timber Colour
<b>Odour:</b>	Characteristic
<b>Melting Point:</b>	Not determined
<b>Boiling Point:</b>	Above 90c
<b>Flashpoint:</b>	Not applicable
<b>Vapour Pressure:</b>	Not determined.
<b>Water Solubility:</b>	Soluble

### INGREDIENTS

<b>Ingredients</b>	<b>CAS No.</b>	<b>Proportion %</b>
<b>Calcium Carbonate</b>	1317-65-3	High
<b>Water</b>	7732-18-5	Medium
<b>Acrylic Copolymer</b>	Not known	Medium
<b>Other non-hazardous</b>	N.A.	Medium

### HEALTH HAZARD INFORMATION

<b>If Inhaled:</b>	Very low vapour so no hazards are foreseen.
<b>Eye contact:</b>	May cause slight irritation from uncured product.
<b>Skin Contact:</b>	May cause slight irritation from uncured product.
<b>If Swallowed:</b>	Available information suggests that no adverse health

## TECHNICAL DATA SHEETS

### FIRST AID

<b>Eye Contact:</b>	Rinse immediately with plenty of water. Seek medical advice if still a problem.
<b>Skin Contact:</b>	Wash immediately with lots of soapy water. If irritation persists, seek medical advice.
<b>After Inhalation:</b>	Remove the victim into fresh air. Never give an unconscious person anything by mouth.
<b>Medical Advice:</b>	Treat as necessary.
<b>If Swallowed:</b>	Do not induce vomiting. Give one glass of water or milk. Seek medical advice.

### FIRE HAZARD

<b>Suitable extinguishing Media:</b>	Quantities of water, Polyvalent Foam, ABC Powder, Carbon Dioxide.
<b>Special exposure hazards:</b>	Non combustible On burning: Releases Carbon Monoxide and other hazards fumes.
<b>Instructions:</b>	No specific fire fighting instructions required.
<b>Special protective equipment for firefighters:</b>	Heat/fire exposure: compressed air/oxygen apparatus.

## TECHNICAL DATA SHEETS

### PRECAUTIONS FOR USE

**Exposure standards ( NOHSC: 1003 (1995)**

**Butyl Acrylate**

**TWA**

**10ppm**

**Personal Protection:**

Use in well ventilated areas. Avoid contact with skin. Wear overalls, safety goggles and PVC gloves. Always wash hands after using this product.

**Flammability:**

This product is not flammable

### FIRST AID

**Handling:**

Keep containers securely sealed and protected against physical damage in their original packages.

**Transport:**

This product is not classified as dangerous goods. Therefore there are no special requirements for transporting the product.

**Accidental Spills:**

Wear face masks for concentrated spill. Wash spillage areas with soapy water to prevent slips. Contact waste authority for disposal.

**Storage:**

Keep out of direct sunlight.  
Store below 40 degrees C.

### DISCLAIMER

This MSDS has been produced with the best knowledge we have at present on the safe use, handling, storage, health and safety hazard. We cannot anticipate or control the conditions under which the product may be used. Each person using this product is advised to study this MSDS before use.